

ALTOS® Lite Loose Tube, Gel-Free, Double-Jacket, Double-Armoured Cable

96 fibres, 50 µm multimode (OM2)

CORNING

Corning ALTOS® Lite gel-free double-jacket, double-armoured cables are rugged cables designed for direct-buried installations. The loose tube design provides stable performance over a wide temperature range and is compatible with any telecommunications-grade optical fibre.

Features and Benefits

Two jacket layers and two steel tape armour layers

Provides superior rodent resistance for direct-buried applications

Flexible, craft-friendly buffer tubes

Facilitate easy routing in closures

Gel-free waterblocking technology

Craft-friendly cable preparation

Medium-density polyethylene jacket

Rugged, durable and easy to strip while providing superior protection against UV radiation, fungus, abrasion and other environmental factors


Exceeds the RDUP requirements for mid-span buffer tube slack storage

Provides flexibility for mid-span access applications


Standards

Approvals and Listings	USDA Rural Development Programs
-------------------------------	---------------------------------

Design And Test Criteria	ANSI/ICEA S-87-640
---------------------------------	--------------------



Part Number: 096TUD-T4131D20



Cross Section of Order Number: 096TUD-T4131D20

ALTOS® Lite Loose Tube, Gel-Free, Double-Jacket, Double-Armoured Cable

96 fibres, 50 µm multimode (OM2)

CORNING

Specifications

General Specifications

Environment	Outdoor
Application	Direct Buried
Cable type	Loose Tube
Product type	Armoured
Fibre Category	50 µm MM (OM2)

Temperature Range

Storage	-40 °C to 70 °C (-40 °F to 158 °F)
Installation and assembly	-30 °C to 70 °C (-22 °F to 158 °F)
Operation	-40 °C to 70 °C (-40 °F to 158 °F)

Cable Design

Central Element	Dielectric
Fibre Count	96
Fibre colouring	Blue, Orange, Green, Brown, Grey, White, Red, Black, Yellow, Violet, Pink, Turquoise
Fibres per tube	12
Number of Tube Positions	8
Number of Active Tubes	8
Buffer tube colour coding	Blue, Orange, Green, Brown, Grey, White, Red, Black
Buffer tube diameter	2.5 mm (0.1 in)
Tape	Water-swellaable
Tensile Strength Elements and/or Armouring - Layer 1	Corrugated steel tape armour
Inner Jacket Material	Polyethylene (PE)
Tape, Layer 2	Water-swellaable
Number of ripcords	4
Tensile strength elements and/or armouring - Layer 2	Corrugated steel tape armour
Outer jacket material	Polyethylene (PE)
Outer jacket colour	Black
Maximum Fibres per Tube	12

ALTOS® Lite Loose Tube, Gel-Free, Double-Jacket, Double-Armoured Cable

96 fibres, 50 µm multimode (OM2)

CORNING

Mechanical Characteristics Cable

Max. tensile strength, short-term	2700 N (600 lbf)
Max. Tensile Strength, Long-Term	890 N (200 lbf)
Weight	297 kg/km (199 lb/1000 ft)
Nominal Outer Diameter	17.8 mm (0.70 in)
Min. Bend Radius Installation	267 mm (10.5 in)
Min. Bend Radius Operation	178 mm (7.0 in)

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Fibre Specifications

Optical Characteristics (cabled)

Fibre core diameter	50 µm
Fibre Category	OM2
Fibre code	T
Performance Option Code	31
Wavelengths	850 nm / 1300 nm
Maximum attenuation	3.0 dB/km / 1.0 dB/km
Serial 1 gigabit ethernet	750 m / 500 m
Serial 10 gigabit ethernet	150 m / -
Min. overfilled launch (OFL) bandwidth	700 MHz*km / 500 MHz*km
Minimum effective modal bandwidth (EMB)	950 MHz*km / -

Notes: 1) 50 µm multimode fibre macrobend loss ≤ 0.2 dB at 850 nm for two turns around 7.5 mm radius mandrel
2) Improved attenuation and bandwidth options available
3) Bend-insensitive single-mode fibres available on request.
4) Contact a Corning Customer Care Representative for additional information

Ordering Information

Part Number	096TUD-T4131D20
Product Description	ALTOS® Lite Loose Tube, Gel-Free, Double-Jacket, Double-Armoured Cable, 96 fibres, 50 µm multimode (OM2)
EAN Code	4056418528618

ALTOS® Lite Loose Tube, Gel-Free, Double-Jacket, Double-Armoured Cable

96 fibres, 50 µm multimode (OM2)

The Corning logo consists of a solid blue square with the word "CORNING" in white, uppercase, sans-serif font centered within it.

CORNING

Notes



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2017 Corning Optical Communications. All rights reserved.