

Closet Connector and Splice Housing (CCS)

Holds 4 CCH connector panels, 2 4R/4S splice trays

CORNING

The closet connector splice housing (CCS) combines the benefits of a connector housing and splice housing into a single unit. This cost-effective design approach reduces the number of housings being installed, saving the user valuable and expensive rack space.

The CCS is a rack-mounted product that is to be used in premises applications in the main cross-connect (MC) or intermediate cross-connect (IC) locations. To optimize the flexibility of this design, Corning recommends the use of pigtailed panels to reduce installation time and improve quality. These panels are available in a variety of connector types and come complete with factory-installed and -tested connectorized pigtails.

Product will fit in either 19- or 23-in equipment racks or cabinets. The housing is built to be mounted in a 19-in rack or cabinet. Optional 23-in brackets are also available. A field-installable lock kit is available for both the front and rear doors.

Features and Benefits

Durable, polycarbonate-tinted front door for viewing jumpers

Ideal for pigtail splicing

Supports single-mode and multimode applications

Suitable for loose tube, tight-buffered and ribbon cables

Offers flexibility for mounting in equipment racks or cabinets

Multiple cable entry and jumper exit locations

Accommodates splice trays for fusion and mechanical splices

Individual splice tray access

Specifications

General Specifications	
Application	Enterprise Networks
Mounting Type	Rack 19-in, Rack 23-in
Product Type	Rack-Mountable Hardware

Closet Connector and Splice Housing (CCS)

Holds 4 CCH connector panels, 2 4R/4S splice trays

CORNING

Design - Hardware

Housing Color	Black
Housing Type	CCS
Height Unit	3U
Locking Availability	Front or rear
Number of Panels per Housing	4
Panel or Module Type	CCH
Splice Tray Options	Up to (2) category 4R, 4S or 4M

Mechanical Characteristics

Dimensions (HxWxD)	13.3 cm x 43.25 cm x 30.5 cm (5.25 in x 17 in x 12 in)
--------------------	--

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Ordering Information

Part Number	CCS-03U-F
Product Description	Closet Connector and Splice Housing (CCS), holds 4 CCH connector panels, 2 4R/4S splice trays
EAN Code	4056418194226

Shipping Information

Units per Delivery	1/1
Shipping Weight	2.7 kg (6 lb)
Package Contents	Housing (fits 19-in rack), with 0.4-in splice tray bracket; installation guide; 4 blank panels; unit ID label; 2 #10-32 x 0.5-in threaded mounting screws; twenty-four 1/8 x 4-in tie wraps, white; spiral wrap, 3 ft; 2 mounting brackets, flush mount; 2 central member strain-relief clamp kits; bracket for mounting UCC clamp; 2 universal cable clamp (UCC) kits with 5 cable inserts; two sheets 80 grit sandpaper, 1-in wide; 4 M6 mounting screws; 4 M6 cage nuts; 8 #10-32 x 0.5-in threaded mounting screws; 4 #12-24 x 0.5-in threaded cut mounting screws

CORNING

Closet Connector and Splice Housing (CCS)

Holds 4 CCH connector panels, 2 4R/4S splice trays

CORNING

Notes



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING