

Eclipse® Hardware Connector Housing, stubbed

4 rack units, 72 F, SC APC connectors, ribbon cable, riser, top-right cable entry, 50 m, Single-mode (OS2)

CORNING

Corning preconnectorized (“stubbed”) optical hardware is equipped with factory-terminated and -tested cable assemblies pre-installed in a variety of hardware products. “Stubbed” hardware is terminated in the factory according to the requirements of the Corning Quality Standards. This ensures connector performance and quality, therefore eliminating the time consuming and costly process of terminating cables in the field. It also reduces the number of part numbers needed for installation and minimizes the line items on an order.

Features and Benefits

Quality tested

Superior performance

Factory-quality termination

Reduces time and cost

Variety of connector and cable types

Various installation options



Part Number: ECL7250066C-C7CV1B

Standards

Approvals and Listings RDUP (RUS) Listed

Specifications

General Specifications

Application	Central Office, Carrier Networks, CATV environments
Mounting Type	Rack 19-in, Rack 23-in
Product Type	Rack-Mountable Hardware
Cable Type Stubbed	Ribbon Riser Indoor Cable
Fiber Category	Single-mode (OS2)

Design - Hardware

Housing Color	Black
Housing Type	Eclipse Hardware
Cable Entry Direction	Top-right
Connectorization Configuration	Standard product (no dual-end connectorization)
Connector Polish	APC

Eclipse® Hardware Connector Housing, stubbed

4 rack units, 72 F, SC APC connectors, ribbon cable, riser, top-right cable entry, 50 m, Single-mode (OS2)

CORNING

Design - Hardware

Fiber Count	72
Height Unit	4U
Panel or Module Type	Eclipse Hardware

Mechanical Characteristics

Cable Length	164.04 ft (50 m)
Dimensions (HxWxD)	17.5 cm x 43.9 cm x 30.2 cm (6.9 in x 17.3 in x 11.9 in)
Number of Cables	1

Design Adapter

Adapter Type	SC
--------------	----

Ordering Information

Part Number	ECL7250066C-C7CV1B
Product Description	Eclipse® Hardware Connector Housing, stubbed, 4 rack units, 72 F, SC APC connectors, Ribbon Cable, Riser, top-right cable entry, 50 m, Single-mode (OS2)
EAN Code	4056418193755

Shipping Information

Units per Delivery	1/1
Package Contents	Eclipse® Hardware Connector Housing, stubbed, 4 rack units, 72 F, SC APC connectors, ribbon cable, riser, top-right cable entry, Single-mode (OS2), 50 m

Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING