

EDGE8™ Housing

1 rack unit, holds up to 18 EDGE8 modules or panels

CORNING

EDGE8™ solutions are high-density preterminated optical cabling solutions with optimized design for Base-8 fiber applications offering industry-leading connector density. With sufficient connector finger access, there is no need for additional tools enabling faster moves, adds, and changes (MACs).

Features and Benefits

Smaller footprint design with Base-8 components in housings

Greater flexibility with six open slots per tray, for easy deployment of EDGE8™ modules and panels

Key identifiers

EDGE8 printed on housing for easy identification as a Base-8 component

Sliding drawer-style hardware with integrated cable routing guides and port identification

Optimized finger access to connectors combined with industry leading port density

Rotatable trunk strain relief parking plates

Allows for rear cable entry direction, as well as the traditional side cable entry

Removable top covers on the 1 U and 2 U housings

Provides easier access to modules and panels

Quick mounting system

Enables one-person installation and depth adjustment of the housing in the rack

High port density with MTP Base-8 system in 1 U housing

72 LC duplex ports (144 fiber) or 72 MTP ports (576 fiber)



Part Number: EDGE8-01U-SP



Part Number: EDGE8-01U-SP

Specifications

EDGE8™ Housing

1 rack unit, holds up to 18 EDGE8 modules or panels

CORNING

General Specifications

Application	Data Center
Product Type	Fiber Optic Hardware
Mounting Type	Rack 19-in

Design - Hardware

Height Unit	1U
Housing Color	Silver
Housing Type	EDGE™
Number of Panels per Housing	18

Mechanical Characteristics

Dimensions (W x D x H)	432 mm x 561 mm x 44 mm (17.0 in x 22.1 in x 1.75 in)
------------------------	---

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	EDGE8-01U-SP
Product Description	EDGE8™ Housing, 1 rack unit, holds up to 18 EDGE8 modules or panels
EAN Code	4056418139777

Shipping Information

Units per Delivery	1/1
Packaging Dimensions (W x D x H)	581 mm x 667 mm x 197 mm (22.9 in x 26.25 in x 7.75 in)
Shipping Weight	8.2 kg (18 lb)

EDGE8™ Housing

1 rack unit, holds up to 18 EDGE8 modules or panels

CORNING

Notes



Corning Optical Communications RF LLC (Corning Gilbert) • 5310 W. Camelback Rd. • Glendale, AZ 85301 USA
800-528-5567 • FAX: 800-344-6358 • International: +1-623-245-1050 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications RF is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications RF is ISO 9001 certified. © 2016 Corning Optical Communications. All rights reserved.

Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-528-5567 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

Page 31 Revision date 2016-03-09

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

CORNING