

Industrial Splice Housing (ISH)

Accepts up to (12) category 2S splice trays



Corning industrial splice housing (ISH) is ideal for manufacturing and industrial applications.

The housing is finished with a baked-on silver-gray powder-coated finish and may be used indoors or outdoors. Wall-mountable for transition splicing between cable at building entrance or pigtail splicing, the ISH provides storage and protection of fiber splices in individually accessible trays. The units have a padlockable outer door.

The ISH is designed to accommodate conduit fittings with the provided plugs and reduction washer, and it accepts standard LANscape® solutions splice trays. The industrial splice housing is also compatible with Corning industrial connector housings ICH-02P-IND, ICH-06P-IND and ICH-12P-IND.

Features and Benefits

NEMA 250-1997 3S and IP64, 65, 66, 67 and 69k tested
Reliability in harsh environments

Accepts standard LANscape® Solutions splice trays
Ease of installation

Keyhole mounting holes
Fast installation

Padlockable with user-supplied padlock
Secure access

Standards

Design and Test Criteria NEMA 250-1997 3S and IP64, 65, 66, 67 and 69k tested

Specifications

General Specifications	
Application	Enterprise Networks
Mounting Type	Wall-Mountable
Product Type	Wall-Mountable Hardware



Industrial Splice Housing (ISH)

Accepts up to (12) category 2S splice trays

CORNING

Design - Hardware

Housing Type	ISH
Splice Tray Options	Up to (12) category 2S splice trays

Mechanical Characteristics

Dimensions (HxWxD)	40.1 cm x 50.8 cm x 15.2 cm (16 in x 20 in x 6 in)
--------------------	--

Ordering Information

Part Number	ISH-12SPT
Product Description	Industrial Splice Housing (ISH), accepts up to (12) Type 2S splice trays

Shipping Information

Units per Delivery	1/1
Shipping Weight	9.1 kg (20 lb)
Package Contents	Housing with installation guide; unit ID label; UCC strain-relief kit; UCC strain-relief bracket; central strength member strain-relief kit; 2 #6-32 SS self-locking nuts; (18) 1/8 x 4-in tie wraps; 3-in gasket washer; 2 reduction washer, 2-in to 1-in

Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. Corning Optical Communications is ISO 9001 certified. © 2014 Corning Optical Communications. All rights reserved.

CORNING