

Pretium® Connector Housing (PCH)

1 rack unit, holds 3 CCHE Plug & Play™ Reduced-Depth Modules

CORNING

The rack-mount Pretium® connector housings (PCH) are available in 1U, 2U and 4U sizes and mount in 19-in racks or cabinets. Combined with the modules, panels, harnesses, trunks and jumpers, they provide a tip-to-tip solution for your fibre optic network.

Features and Benefits


Compatible with Plug & Play™ Systems modules
Designed to support Plug & Play Systems applications

Splice in the housing
Saves rack space and the cost of the second housing

Removable top (1U, 2U)
Maximizes ease of access

Transparent front door (04U and 02U)
Permits viewing while protecting installed patch cords

Large removable fiber guides in front
Effectively manage high patch cord densities



Pretium 3-Module Housing PCH-M3-01U (open) | Photo LAN995

Standards

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
UL-Listed	United States and Canadian safety standards

Specifications

General Specifications	
Application	Enterprise Networks, Data Centre
Mounting type	Rack 19", Rack 23"
Product type	Rack-Mountable Hardware

Design - Hardware	
Housing type	PCH
Housing Colour	grey
Fibre Capacity	Up to 36 fibres installing SC/ST®/SC Duplex connectors, or up to 72 installing LC Duplex or MTRJ connectors

Pretium® Connector Housing (PCH)

1 rack unit, holds 3 CCHE Plug & Play™ Reduced-Depth Modules

CORNING

Design - Hardware

Height Unit	1U
Number of Panels per Housing	3
Panel or Module Type	CCH

Mechanical Characteristics

Dimensions (W x D x H)	426.72 mm x 323.85 mm x 44.45 mm (16.8 in x 12.75 in x 1.75 in)
------------------------	---

Ordering Information

Part Number	PCH-M3-01U
Product Description	Pretium® 3-Module Housing, 1 rack unit, holds three CCHE Plug & Play™ reduced-depth modules
EAN Code	4056418191812

Shipping Information

Units Per Delivery	1/1
Packaging Dimensions (W x D x H)	511.3 mm x 438.15 mm x 120.65 mm (20.13 in x 17.25 in x 4.75 in)
Shipping Weight	1.75 kg (3.85 lb)
Package Contents	Housing; installation guide; 3 blank panels; unit ID label; 4 #10-32 x 50 screws; 4 #12-24 x 50 screws



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY

00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2016 Corning Optical Communications. All rights reserved.