

Fiber Zone Box

4 rack units, holds 12 CCH panels or modules

CORNING

Corning fiber zone box is a cabling infrastructure distribution facility for passive applications in zone cabling. It is ideal for interconnect or crossconnect points in data center zone or horizontal LAN distribution areas. Sized to fit a 2 x 2 ft drop ceiling or subfloor opening, it can also be mounted to a wall and is equipped with a seal to inhibit dust and liquid penetration. The box accepts up to 12 LANscape® solutions CCH connector panels, modules or splitter modules for LC duplex, SC, SC duplex, FC, ST® compatible and MTP® connector fiber termination and distribution as well as up to 24 buffer tube fan-out kits.

Features and Benefits

Removable backplate

Eases installation

Robust lock

Additional security

UL-Listed to United States and Canadian standards, NEMA 1, 2, 5, 12K rated

Safety

Includes 4U of 19-in rack space

Copper and fiber options

Multiposition bulkhead

Dramatically increases ease of use in subfloor/overhead applications



Part Number: FZB-04U

Standards

Approvals and Listings

UL-Listed to the United States and Canadian safety standards, NEMA, 1, 2, 5, 12K rated

RoHS

Free of hazardous substances according to RoHS 2002/95/EG

CORNING

Fiber Zone Box

4 rack units, holds 12 CCH panels or modules

CORNING

Specifications

General Specifications

Application	Enterprise Networks, Data Center
Mounting Type	Wall-Mountable, Ceiling mount, Floor mount
Product Type	Wall-Mountable Hardware

Design - Hardware

Housing Type	FZB
Housing Color	white
Number of Panels per Housing	12
Panel or Module Type	CCH
Splice Tray Options	Accommodates up to (12) 0.2 in or (6) 0.4 in category S, or category R splice trays

Mechanical Characteristics

Dimensions (HxWxD)	54 cm x 54 cm x 21.6 cm (21.25 in x 21.25 in x 8.5 in)
--------------------	--

Ordering Information

Part Number	FZB-04U
Product Description	Fiber Zone Box, 4 rack units, holds 12 CCH panels or modules

Shipping Information

Units per Delivery	1/1
Package Contents	Housing; installation guide; label, unit ID; label, port identification for 12 panels; 12 blank panels; 12 tie wraps, 1/8 x 4, white; edge grommet, nylon, 12-in; 32 screws, #6-32 x 0.25-in; 2 Universal Cable Clamp (UCC) Kits with 5 cable inserts; 2 brackets for mounting UCC clamp; 2 fan-out brackets; 4 wall-/floor-mounting brackets; 2 trim plates, floor, FZB-04U; 6 6-32 x .25 Phillips; ground bar EM4250-3550; 2 screws, #8-32 and 2 lock washers, #8
Shipping Weight	15 lb (6.8 kg)

CORNING

Fiber Zone Box

4 rack units, holds 12 CCH panels or modules

The Corning logo is a blue square with the word "CORNING" in white, serif, uppercase letters centered within it.

CORNING

Notes



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.
Corning Optical Communications is ISO 9001 certified. © 2014 Corning Optical Communications. All rights reserved.