

Mini Wall-Mountable Building Terminal (WBM) with Adapters

12 F, SC adapters, with splice tray

CORNING

The Corning mini wall-mountable building terminal (WBM) is a compact interconnect and splice housing for up to 12 optical fibers. It is ideal for building entrance terminals, wiring closets, computer rooms and other controlled environments.

Twelve fibers can be accommodated using 12-fiber LDC panels (SC only). Mass and single-fiber splicing with heat-shrink protection are among the supported options. The WBM unit is available with adapters only, pigtailed or stubbed.

Features and Benefits

Compact size (H x W x D): 6.3 x 10.6 x 2.5 in
Ideal for small locations

Separate Carrier Networks and subscriber outdoors
Minimizes disturbance of splice chamber

Available empty, pigtailed or stubbed
Configurable



Part Number: WBM-012-123C



Part Number: WBM-012-123C

CORNING

Mini Wall-Mountable Building Terminal (WBM) with Adapters

12 F, SC adapters, with splice tray

CORNING

Specifications

General Specifications

Application	Customer premises environments, Carrier Networks
Mounting Type	Wall-Mountable
Product Type	Wall-Mountable Hardware
Fiber Category	Single-mode (OS2)

Design - Hardware

Housing Type	WBM
Connector Polish	UPC
Fiber Count	12
Number of Adapters	12
Panel or Module Type	LHC

Mechanical Characteristics

Dimensions (HxWxD)	16 cm x 27 cm x 6.4 cm (6.3 in x 10.6 in x 2.5 in)
--------------------	--

Design Adapter

Adapter Type	SC
--------------	----

Ordering Information

Part Number	WBM-012-123C
Product Description	Mini Wall-Mountable Building Terminal (WBM) with adapters, SC, 12 F, with splice tray
EAN Code	4056418189024

Shipping Information

Units per Delivery	1/1
Shipping Weight	0.93 kg (2.5 lb)
Package Contents	Mini Wall-Mountable Building Terminal (WBM), 12 F, SC Adapters, ships with Splice Tray, 3/4-in connector fitting, 5 fitting inserts (select one for cable size) and cable ties

Mini Wall-Mountable Building Terminal (WBM) with Adapters

12 F, SC adapters, with splice tray

The Corning logo is a blue square with the word "CORNING" in white, serif, uppercase letters centered within it.

CORNING

Notes

Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.